

## **Data Sheet**



# PC Lite Polycarbonate Compact Sheet Type: Compact 3mm

## Overview

PC Lite Polycarbonate Sheets as well as Polycarbonate Rolls have high impact strength and are also high temperature resistant. Both have special co-extruded ultra violet (UV) protection. Virtually unbreakable, and yet as transparent as glass with less than half its weight, Compact Sheets are easy to fabricate as well as to install. Known for their excellent insulation properties, these sheets are suitable for cutting, drilling, bending and thermoforming as well.

# Typical Physical Properties

· · · · · · · · · · · · · · · · · · ·	•		
Property		Units	Value
Overall thickness		mm	3
Area weight		kg/ SQM	3.6
Standard widths*		mm	1220
Standard lengths*		mm	2440
	Clear	%	80
Light transmission			
Min. cold bending radius		m	4
Service Temperature	Short term	°C	-40 to 120
	Long term	°C	-40 to 100
Practical thermal expansion/contraction	range	mm/m	3
Coefficient of linear thermal expansion		mm/m °C	0.065
of linear thermal expansion		mm/m °C	0.065

### **IMPACT STRENGTHS**

Property	Units	Value	
Low frequencies pre-dominant		21 db	
High frequencies predominant		29 db	

### CORPORATE OFFICE

GD ITL Twin Tower B-09 201-201A, Second Floor, Netaji Subhash Palace, New Delhi - 110034, India

Mobile: <u>+91-9818411482</u>

Website: www.mgpolyplast.com